SAFETY DATA SHEET

Version 5.9 Revision Date 12/16/2016 Print Date 04/08/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Bradford Reagent

Product Number : B6916 Brand : Sigma

Product Use : For laboratory research purposes.

Supplier : Sigma-Aldrich Canada Co. Manufactur : Sigma-Aldrich Corporation

2149 Winston Park Drive er 3050 Spruce St.

OAKVILLE ON L6H 6J8 St. Louis, Missouri 63103

USA

Telephone : +1 9058299500 Fax : +1 9058299292

Emergency Phone # (For

Preparation Information

both supplier and manufacturer)

oth supplier and

Product Safety - Americas Region

Sigma-Aldrich Corporation

+1-703-527-3887 (CHEMTREC)

1-800-521-8956

CANADA

2. HAZARDS IDENTIFICATION

Emergency Overview

Target Organs

Ε

Liver, Blood, Bone marrow, Eyes, Kidney, Heart, Central nervous system

WHMIS Classification

D1B Toxic Material Causing Immediate and Serious Toxic by ingestion

Toxic Effects
Corrosive Material
Toxic by skin absorption

Specific target organ toxicity - single exposure

Corrosive

GHS Classification

Corrosive to metals (Category 1)
Acute toxicity, Oral (Category 5)
Skin corrosion (Category 1B)
Serious eye damage (Category 1)

Specific target organ toxicity - single exposure (Category 1)

GHS Label elements, including precautionary statements

Danger

Hazard statement(s)

Pictogram

Signal word

H290 May be corrosive to metals.H303 May be harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H370 Causes damage to organs.

Precautionary statement(s)

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Sigma - B6916 Page 1 of 9

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

HMIS Classification

Health hazard: 3
Chronic Health Hazard: *
Flammability: 0
Physical hazards: 0

Potential Health Effects

Inhalation Toxic if inhaled. Material is extremely destructive to the tissue of the mucous

membranes and upper respiratory tract.

Skin Toxic if absorbed through skin. Causes skin burns.

Eyes Causes eye burns. **Ingestion** Toxic if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Coomassie[™] dye binding protein assay, Protein dye reagent

CAS-No.	EC-No.	Index-No.	Concentration
Phosphoric acid			
7664-38-2	231-633-2	015-011-00-6	10 %
Methanol			
67-56-1	200-659-6	603-001-00-X	4 %
Water			
7732-18-5	231-791-2	-	85.99 %

Hydrogen [4-[4-(p-ethoxyanilino)-4'-[ethyl(m-sulphonatobenzyl)amino]-2'-methylbenzhydrylene]-3-methylcyclohexa-2,5-dien-1-ylidene](ethyl)(m-sulphonatobenzyl)ammonium, monosodium salt 6104-58-1 228-058-4 - 0.004 %

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Not flammable or combustible.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Sigma - B6916 Page 2 of 9

Special protective equipment for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Hazardous combustion products

Explosion data - sensitivity to mechanical impact

No data available

Explosion data - sensitivity to static discharge

No data available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis	
Phosphoric acid	7664-38-2	TWA	1.000000 mg/m3	Canada. British Columbia OEL	
		STEL	3.000000 mg/m3	Canada. British Columbia OEL	
		TWA	1.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)	
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required				
		STEL	3.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)	
	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required				
		TWAEV	1.000000 mg/m3	Canada. Ontario OELs	
		STEV	3.000000 mg/m3	Canada. Ontario OELs	
		TWAEV	1 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants	
		TWAEV	1.000000	Québec. Regulation respecting occupational health	

Sigma - B6916 Page 3 of 9

			mg/m3	and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
		STEV	3 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
		STEV	3.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
		TWA	1.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
		TWA	1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
		STEL	3.000000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
		STEL	3 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
Methanol	67-56-1	TWA	200.000000 ppm 262.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
Remarks	Substance	Substance may be readily absorbed through intact skin					
		STEL	250.000000 ppm 328.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
	Substance may be readily absorbed through intact skin		ugh intact skin				
		TWA	200.000000 ppm	Canada. British Columbia OEL			
	Contributes	significantly	to the overall exp	posure by the skin route.			
		STEL	250.000000 ppm	Canada. British Columbia OEL			
	Contributes	significantly	to the overall exp	oosure by the skin route.			
		TWAEV	200.000000 ppm 262.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
	Skin (percu	Skin (percutaneous)					
		STEV	250.000000 ppm 328.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
	Skin (percu	taneous)					
		TWA	200 ppm 262 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
	Substance	may be read	lily absorbed throu	ugh intact skin			
		STEL	250 ppm 328 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			

Sigma - B6916 Page 4 of 9

Substance	may be readi	ily absorbed throu	ugh intact skin		
	TWA	200 ppm	Canada. British Columbia OEL		
Contributes	Contributes significantly to the overall exposure by the skin route.				
	STEL	250 ppm	Canada. British Columbia OEL		
Contributes	significantly	to the overall exp	posure by the skin route.		
	TWAEV	200 ppm 262 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants		
Skin (percu	taneous)				
	STEV	250 ppm 328 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants		
Skin (percu	Skin (percutaneous)				
	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	STEL	250.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)		

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

Sigma - B6916 Page 5 of 9

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Specific engineering controls

Use mechanical exhaust or laboratory fumehood to avoid exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid, clear

Colour No data available

Safety data

No data available pН

Melting

No data available point/freezing point

Boiling point No data available Flash point No data available

No data available Ignition temperature

Auto-ignition temperature

No data available

No data available Lower explosion limit No data available Upper explosion limit No data available Vapour pressure

1.066 g/cm3 at 20 °C (68 °F) Density

Water solubility No data available Partition coefficient: No data available

n-octanol/water

Relative vapour

No data available

density

No data available Odour Odour Threshold No data available No data available Evaporation rate

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No data available

Sigma - B6916 Page 6 of 9

Conditions to avoid

No data available

Materials to avoid

Strong bases, Powdered metals

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Thermal decomposition may produce toxic fumes of phosphorus oxides and/or phosphine

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Oxides of phosphorus

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

No data available

Inhalation LC50

No data available

Dermal LD50

No data available

Other information on acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

Eyes: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

No data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

No data available

Aspiration hazard

No data available

Potential health effects

Inhalation Toxic if inhaled. Material is extremely destructive to the tissue of the mucous membranes

and upper respiratory tract.

Ingestion Toxic if swallowed.

Skin Toxic if absorbed through skin. Causes skin burns.

Eyes Causes eye burns.

Sigma - B6916 Page 7 of 9

Signs and Symptoms of Exposure

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects

No data available

Additional Information

RTECS: Not available

12. ECOLOGICAL INFORMATION

Toxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

PBT and vPvB assessment

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1805 Class: 8 Packing group: III

Proper shipping name: Phosphoric acid solution

Reportable Quantity (RQ): Marine pollutant: No

Poison Inhalation Hazard: No

IMDG

UN number: 1805 Class: 8 Packing group: III EMS-No: F-A, S-B

Proper shipping name: PHOSPHORIC ACID SOLUTION

Marine pollutant: No

IATA

UN number: 1805 Class: 8 Packing group: III

Proper shipping name: Phosphoric acid, solution

15. REGULATORY INFORMATION

WHMIS Classification

D1B Toxic Material Causing Immediate and Serious

Toxic Effects

E Corrosive Material

Toxic by ingestion

Toxic by skin absorption

Specific target organ toxicity - single exposure

Corrosive

Sigma - B6916 Page 8 of 9

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

16. OTHER INFORMATION

Text of H-code(s) and R-phrase(s) mentioned in Section 3

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Sigma - B6916 Page 9 of 9