

SAFETY DATA SHEET

Creation Date 27-April-2009

Revision Date 18-January-2018

Revision Number 6

1. Identification

A408-1; A408-4; A408-4LC; A408SK-4

Methanol

Cat No. :

Product Name

CAS-No Synonyms 67-56-1 Methyl alcohol

Recommended Use Uses advised against Laboratory chemicals. Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company Importer/Distributor Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6, Canada Tel: 1-800-234-7437

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification

Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Manufacturer

Fisher Scientific

One Reagent Lane Fair Lawn, NJ 07410

Tel: (201) 796-7100

Flammable liquids	Category 2
Acute oral toxicity	Category 3
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity	Category 3
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Optic nerve.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, spleen, Blood.	

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor Toxic if swallowed, in contact with skin or if inhaled Causes damage to organs Causes damage to organs through prolonged or repeated exposure



Precautionary Statements Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER/ doctor

Rinse mouth

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Poison, may be fatal or cause blindness if swallowed

3. Composition/Information on Ingredients

Component	CAS-No	Weight %			
Methyl alcohol	67-56-1	>95			
4. First-aid measures					

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket

	mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately.
Most important symptoms/effects	Breathing difficulties. May cause blindness: Inhalation of high vapor concentrations may
Notes to Physician	cause symptoms like headache, dizziness, tiredness, nausea and vomiting Treat symptomatically
	5. Fire-fighting measures
Suitable Extinguishing Media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	12 °C / 53.6 °F
Method -	No information available
Autoignition Temperature	455 °C / 851 °F
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO) Formaldehyde

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPAHealth	Flammability	Instability	Physical hazards			
1	3	0	N/A			
	6. Accidental re	lease measures				
Personal Precautions	personal protective equipr Take precautionary measu	nent. Ensure adequate ventilat ures against static discharges.	om and upwind of spill/leak. Use tion. Remove all sources of ignition.			
Environmental Precautions	information.	o the environment. See Sectio	in 12 for additional ecological			
Methods for Containment and Up	Clean Soak up with inert absorbe Remove all sources of ign	ent material. Keep in suitable, d ition. Use spark-proof tools and				
7. Handling and storage						
Handling	eyes, on skin, or on clothir away from open flames, h To avoid ignition of vapors	ng. Use only under a chemical ot surfaces and sources of ign	oors or spray mist. Do not get in fume hood. Do not ingest. Keep ition. Use only non-sparking tools. all metal parts of the equipment st static discharges.			
Storage	Keep container tightly clos	ed in a dry and well-ventilated	place. Keep away from open			

flames, hot surfaces and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Skin	TWA: 200 ppm STEL: 250 ppm Skin	TWA: 200 ppm STEL: 250 ppm Skin	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Skin	STEL: 250 ppm Skin	(Vacated) TWA: 260 mg/m ³	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Hand Protection	Tightly fitting safety goggles Protective gloves		
Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	> 480 minutes	0.35 mm	As tested under EN374-3
Viton (R)	> 480 minutes	0.70 mm	Determination of Resistance to

Permeation by Chemicals Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

	9. Physical and chemical properties			
Physical State	Liquid			
Appearance	Colorless			
Odor	Alcohol-like			
Odor Threshold	No information available			
рН	Not applicable			
Melting Point/Range	-98 °C / -144.4 °F			
Boiling Point/Range	64.7 °C / 148.5 °F @ 760 mmHg			
Flash Point	12 °C / 53.6 °F			
Evaporation Rate	5.2 (ether = 1)			
Flammability (solid,gas)	Not applicable			
Flammability or explosive limits				
Upper	31.00 vol %			
Lower	6.0 vol %			
Vapor Pressure	128 hPa @ 20 °C			
Vapor Density	1.11			
Specific Gravity	0.791			
Solubility	Miscible with water			
Partition coefficient; n-octanol/w	ater No data available			
Autoignition Temperature	455 °C / 851 °F			
Decomposition Temperature	No information available			
Viscosity	0.55 cP at 20 °C			
Molecular Formula	C H4 O			
Molecular Weight	32.04			
VOC Content(%)	100			
Surface tension	0.02255 N/m @ 20°C			

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases, Metals, Peroxides
Hazardous Decomposition Product	s Carbon monoxide (CO), Formaldehyde
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component information			
Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	Calc. ATE 60 mg/kg LD50 > 1187 – 2769 mg/kg (Rat)	Calc. ATE 60 mg/kg LD50 = 17100 mg/kg(Rabbit)	Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists) LC50 = 128.2 mg/L (Rat) 4 h
Toxicologically Synergistic Products	Carbon tetrachloride		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation		May cause skin and eye irritation				
Sensitization		No information available				
Carcinogenicity		The table below in	dicates whether ea	ach agency has list	ed any ingredient	as a carcinogen.
Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed
Mutagenic Effects		No information ava	ailable			
Reproductive Effect	s	No information ava	iilable.			
Developmental Effe	cts	Component substance is listed on California Proposition 65 as a developmental hazard.				
Teratogenicity		No information available.				
STOT - single expos STOT - repeated exp		Optic nerve Kidney Liver spleen Blood				
Aspiration hazard		No information available				
Symptoms / effects delayed	,both acute and	d May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting				
Endocrine Disrupto	r Information	No information available				
Other Adverse Effect	cts	The toxicological properties have not been fully investigated.				

12. Ecological information

Ecotoxicity

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea		
Methyl alcohol	Not listed	Pimephales promelas: LC50		EC50 > 10000 mg/L 24h		
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min			
			EC50 = 43000 mg/L 5 min			
Persistence and Degradability Persistence is unlikely based on information available.						
Bioaccumulation/Accum	No informati	No information available.				
Mobility	Will likely be	Will likely be mobile in the environment due to its volatility.				

Component	log Pow
Methyl alcohol	-0.74

13. Disposal considerations

Waste Disposal Methods

Should not be released into the environment.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	<u>-</u>

14. Transport information		
DOT UN-No Proper Shipping Name Hazard Class Packing Group TDG UN-No	UN1230 METHANOL 3 II UN1230	

Proper Shipping Name Hazard Class Subsidiary Hazard Class Packing Group	METHANOL 3 6.1 II
IATA UN-No	UN1230
••	
Proper Shipping Name	METHANOL
Hazard Class	3
Subsidiary Hazard Class	6.1
Packing Group	II
IMDG/IMO	
UN-No	UN1230
Proper Shipping Name	METHANOL
Hazard Class	3
Subsidiary Hazard Class	6.1
Packing Group	II
	15. Regulatory information

International Inventories

Component	DSL	NDSL	TSCA	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Methyl alcohol	Х	-	Х	200-659-6	-		Х	Х	Х	Х	Х

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Methyl alcohol	Part 1, Group A Substance Part 5, Individual Substances		

	16. Other information
Prepared By	Regulatory Affairs
	Thermo Fisher Scientific
	Email: EMSDS.RA@thermofisher.com
Creation Date	27-April-2009
Revision Date	18-January-2018
Print Date	18-January-2018
Revision Summary	This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS