SAFETY DATA SHEET

Version 5.9 Revision Date 06/22/2018 Print Date 03/04/2019

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Acetic acid

Product Number : 45726 Brand : Sigma Index-No. : 607-002-00-6

CAS-No. : 64-19-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Canada Co.

2149 Winston Park Drive OAKVILLE ON L6H 6J8

CANADA

Telephone : +1 9058299500 Fax : +1 9058299292

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)

Flammable liquids (Category 3), H226 Corrosive to metals (Category 1), H290 Skin corrosion (Category 1A), H314 Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H226 Flammable liquid and vapour. H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. Keep container tightly closed. Keep only in original packaging.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P233

P234

P242 Use non-sparking tools. P243 Take action to prevent static discharges. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove P305 + P351 + P338 + P310 contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P363 Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to P370 + P378 extinguish. Absorb spillage to prevent material damage. P390 Store in a well-ventilated place. Keep cool. P403 + P235 P405 Store locked up.

Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

P501

Synonyms : Glacial acetic acid

Registration number : 01-2119475328-30-XXXX

Hazardous components

Component	Classification	Concentration*
Acetic acid		
	Flam. Liq. 3; Met. Corr. 1; Skin Corr. 1A; Eye Dam. 1; H226, H290, H314	90 - 100 %
* Weight percent		

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

Sigma - 45726 Page 2 of 8

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Moisture sensitive.

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control	Basis
			parameters	

Acetic acid	64-19-7	TWA	10 ppm 25 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	15 ppm 37 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	10 ppm	Canada. British Columbia OEL
		STEL	15 ppm	Canada. British Columbia OEL
		TWAEV	10 ppm 25 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	15 ppm 37 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)

Derived No Effect Level (DNEL)

Application Area	Exposure routes	Health effect	Value
Workers	Inhalation	Acute local effects	25 mg/m3
Workers	Inhalation	Long-term local effects	25 mg/m3
Workers	Skin contact	Long-term local effects	10mg/kg BW/d
Consumers	Inhalation	Acute local effects	25 mg/m3
Consumers	Inhalation	Long-term local effects	25 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value	
Soil	0.478 mg/kg	
Marine water	0.3058 mg/l	
Fresh water	3.058 mg/l	
Marine sediment	1.136 mg/kg	
Fresh water sediment	11.36 mg/kg	
Sewage treatment plant	85 mg/l	
Aquatic intermittent release	30.58 mg/l	

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Sigma - 45726 Page 4 of 8

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene Minimum layer thickness: 0.6 mm Break through time: 32 min

Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

> Appearance Form: liquid

> > Colour: colourless

Odour b) pungent

Odour Threshold No data available 2.4 at 60.05 g/l d) рH

Melting point/freezing

point

Melting point/range: 16.2 °C (61.2 °F) - lit.

Initial boiling point and

boiling range

117 - 118 °C (243 - 244 °F) - lit.

g) Flash point 40.0 °C (104.0 °F) - closed cup

h) Evaporation rate No data available Flammability (solid, gas) No data available

Upper/lower Upper explosion limit: 19.9 %(V) j) flammability or Lower explosion limit: 4 %(V)

explosive limits

k) Vapour pressure 73.3 hPa (55.0 mmHg) at 50.0 °C (122.0 °F)

15.2 hPa (11.4 mmHg) at 20.0 °C (68.0 °F)

Page 5 of 8

Vapour density No data available

m) Relative density 1.049 g/cm3 at 25 °C (77 °F)

n) Water solubility completely miscible

o) Partition coefficient: n-

octanol/water

log Pow: -0.17

Auto-ignition 485.0 °C (905.0 °F)

Sigma - 45726

temperature

q) Decomposition No data available

temperature

r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties No data available

9.2 Other safety information

Surface tension 28.8 mN/m at 10.0 °C (50.0 °F)

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Oxidizing agents, Soluble carbonates and phosphates, Hydroxides, Metals, Peroxides, permanganates, e.g. potassium permanganate, Amines, Alcohols, Nitric acid

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 3,310 mg/kg

LC50 Inhalation - Mouse - 1 h - 5620 ppm

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Eye: Conjunctive irritation. Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Eye: Other. Blood: Other changes.

LC50 Inhalation - Rat - 4 h - 11.4 mg/l

LD50 Dermal - Rabbit - 1,112 mg/kg

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes severe burns.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Corrosive to eyes

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: AF1225000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Ingestion or inhalation of concentrated acetic acid causes damage to tissues of the respiratory and digestive tracts. Symptoms include: hematemesis, bloody diarrhea, edema and/or perforation of the esophagus and pylorus, pancreatitis, hematuria, anuria, uremia, albuminuria, hemolysis, convulsions, bronchitis, pulmonary edema, pneumonia, cardiovascular collapse, shock, and death. Direct contact or exposure to high concentrations of vapor with skin or eyes can cause: erythema, blisters, tissue destruction with slow healing, skin blackening, hyperkeratosis, fissures, corneal erosion, opacification, iritis, conjunctivitis, and possible blindness., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - > 1,000 mg/l -

96 h

(OECD Test Guideline 203)

Toxicity to daphnia and

other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - > 300.82 mg/l - 48 h

(OECD Test Guideline 202)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 30 d

Result: 99 % - Readily biodegradable. Remarks: Expected to be biodegradable

Biochemical Oxygen

Demand (BOD)

880 mg/g

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Additional ecological

information

No data available

Sigma - 45726 Page 7 of 8

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

TDG (Canada)

UN number: 2789 Class: 8 (3) Packing group: II

Proper shipping name: ACETIC ACID, GLACIAL

IMDG

IATA

UN number: 2789 Class: 8 (3) Packing group: II

Proper shipping name: Acetic acid, glacial

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Dam. Serious eye damage Flam. Liq. Flammable liquids

H226 Flammable liquid and vapour. H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Met. Corr. Corrosive to metals

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Version: 5.9 Revision Date: 06/22/2018 Print Date: 03/04/2019

Sigma - 45726 Page 8 of 8